

DryMix Processing

Spring-Loaded Pressure Relief Valves VCP

23



Description ▼

VCP Pressure Relief Valves consist of a cylindrical casing with a bottom flange to be connected with a spigot welded on the silo roof, a disc shape inner steel lid for negative pressure operation held in position by a central spring rod, an outside steel ring for excess pressure kept in position by three spring rods, gaskets, and a weather protection cover.

Function ▼

In the VCP Pressure Relief Valve, helical springs keep the valve lids closed as long as the pressure value remains within the preset limits. The three outside spring rods keep the external ring-shaped lid firmly closed as long as the force generated by the pressure inside the silo does not overcome the spring force. Once the pressure exceeds the preset value the lid is pushed up and the pressure can escape. The smaller lid covers the central circular opening of the external lid from below. It is held in the middle by a single spring rod and is pressed onto the external lid by the normal air pressure inside the silo. In the event of suction pressure, the spring is compressed and allows the lid to drop. The air entering the silo from outside ensures rapid pressure balance and pushes the central lid back up into the "closed" position.



Application ▼

VCP Pressure Relief Valves are the last resort if abnormal pressure conditions endanger the silo structure. This is why sudden excess or suction pressure inside the silo must be dealt with instantaneously.

Even though ideally a Pressure Relief Valve should never have to go into action, it must be efficient and reliable when needed.

With tens of thousands of units installed worldwide, VCP Pressure Relief Valves have given evidence of being totally reliable under the most different conditions.

Benefits ▼

- ✓ **Used with different materials in the same configuration;**
- ✓ **Easy to handle and fit thanks to lightweight design and reduced overall dimensions;**
- ✓ **Maintenance-friendly thanks to small numbers of components.**

DryMix Processing

Spring-Loaded Pressure Relief Valves VCP



Technical Features / Performance ▼

- ▶ Carbon steel body (VCP...1C) painted RAL 7001
- ▶ Size 273mm (11 in) or 375mm (14 in)
- ▶ Weather protection cover in stainless steel
- ▶ Air volume up to 13,000 m³/h (7,650 cfm)
- ▶ Setting range: excess pressure from 300mm H₂O (0.44psi) up to 800mm H₂O (1.16 psi)
- ▶ Setting range: negative pressure from -50mm H₂O (0.07psi) up to -100mm H₂O (0.15psi)
- ▶ No welding seams inside
- ▶ Equipped for inductive signalling sensors
- ▶ Protective bellows for springs

Overall Dimensions ▼

	Size 273 mm	Size 375 mm
A	400	525
B	356	468
C	125	175
D	120	120
E	325	400
Ø F	273	356
kg	9.5	23

